

Platinum CFW System



Specifications

- 20 kHz HF technology
- 30 kW rating
- kVp range: 40-125 in 1 kV increments
- 12 mA stations
- mAs range: 0.1 - 420 mAs with over 100 mAs selections
- Anatomical programmed with large LCD
- LCD display of all technique factors
- LCD display of bucky, film speed, distance and F.S.
- Auto adjust techniques for bucky, SID and patient conditions
- Built-in tube protection
- Programmable anatomical menus and parameters
- 25' interconnect cable
- UL classified

Tubestand

- Floor to wall or floor to ceiling tubestand with 5 ft. rails
- Electrical locks
- Angulation dial and operator handgrips
- Rotational tubemount

Wallstand

- Stationary front, full length vertical structure, 76" x 24", specify floor stand size
- Grid cabinet: 17 x 17
- Grid: 8:1 ratio, 103 LPI
- Heavy-duty cassette tray
- Electric lock

X-ray Tube

- 1.0 - 2.0 mm F.S.
- 200,000 H.U. with 180 degree horns

Cables

- 15" high voltage cables with federal terminations
- 5-year warranty

Collimator

- Certified manual collimator with light field
- Swivel mount
- 5-year warranty



MEDTEC
MARKETING LIMITED

Medtec / Summit Canada

Proud Distributor & Servicer of Summit Products

Reliable performance...economical price - that's value!